

SAFETY DATA SHEET

1 - IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND COMPANY

Identification of the substance or preparation:

Name: GENTLE CLEANSING GEL Easy Piercing

Product Code: P00289V02/02

Corporate ID / Company:

Company Name: CHEMICAL MANUFACTURING ARDECHOISE. / MBA

Address: THE ISLAND FERAYS.07300.TOURNON cedex. FRANCE./55 RUE NANCY NANTES 44300

Phone: 04-75-07-82-10. Fax: 04-75-07-16-89. / Phone: 02 51 83 05 49. Fax: 02 51 84 10 36

menager@fareva.com

<http://www.fareva.com/>

Phone number of emergency call: +33 (0) 1.45.42.59.59.

Company / Organisation: INRS / ORFILA <http://www.centres-antipoison.net>.

Use of the substance / preparation:

COSMETIC

2 - HAZARDS IDENTIFICATION

This product is classed: Highly flammable.

Risk of irritation to the eyes.

Other data:

This product is rinsed for cosmetic purposes.

Flammability test calculated in accordance with Directive 2008/47/EC.

Pressurized container.

3 - COMPOSITION / INFORMATION ON INGREDIENTS

Text of risk phrases appearing in section 3: see section 16.

Hazardous substances present

(Present in the preparation at a concentration sufficient to give it the toxicological characteristics it would have in pure 100%).

This preparation contains no hazardous substance in this category.

Other substances representing a hazard:

CAS	CE	Name	Symb.	R:	%
68439-50-9	500-213-3	Alcohol Ethoxylate C12-C14	Xi N	R41 R50	0 <= x% <2.5
61789-40-0	263-058-8	cocamidopropylbetaine	Xi	R36 R52	0 <= x% <2.5
68155-06-6	268-934-3	FATTY ACID AMIDE	Xi	R41 R38	0 <= x% <2.5
68891-38-3	500-234-8	Fatty Alcohol Sulfate C12-14 Ethoxylated SODIUM SALT	Xi	R38 R41	2.5 <= x% <10

Substances present at a concentration below the minimum danger threshold:

No known substance in this category present.

Other substances with occupational exposure limits:

CAS	CE	Name	Symb.	R:	%
106-97-8	203-448-7	BUTANE (CONTAINING LESS OF 0.1% BUTADIENE)	F +	R12	2.5 <= x% <10

4 - FIRST AID

Generally, if in doubt or if symptoms persist, always consult a doctor.

NEVER give anything by mouth to an unconscious person.

In case of inhalation:

Remove to fresh air at rest.

In the event of splashes or contact with eyes:

Wash thoroughly with clean, fresh water for 15 minutes holding the eye open.

Refer the patient to an ophthalmologist, especially if there is any redness, pain or visual impairment.

Whatever the initial state, refer the patient to an ophthalmologist, pointing to the label.

In the event of splashes or contact with skin:

If irritation occurs, rinse thoroughly with water. Consult a dermatologist if the feeling persists.

If swallowed:

If swallowed, if the quantity is small (not more than one mouthful), rinse the mouth with water and consult a doctor

Immediately call a physician and show this label.

5 - CONTROL MEASURES AGAINST FIRE

Dry chemicals, carbon dioxide and other extinguishing gas are suitable for small fires.

Extinguishing methods not to use for safety reasons:

Cool containers near the flames to avoid the risk of bursting under pressure.

Prevent the effluent of the fight against the fire from entering drains or watercourses.

Do not use compressed air for filling, discharging, or handling.

Special protective equipment for staff employed in the fight against fire:

The participants will be equipped with autonomous insulated breathing protection.

6 - MEASURES IN CASE OF ACCIDENTAL RELEASE

Personal precautions:

Avoid breathing vapors.

Avoid contact with skin and eyes.

Refer to protective measures listed in sections 7 and 8.

Prevent any risk of ignition of vapors.

Eliminate the flames in the area concerned.

Spills may cause slippery floors.

Precautions for environmental protection:

Contain and collect spillage with non-combustible absorbent materials eg sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent entry into sewers or waterways.

Place in container for disposal of waste recovered in accordance with regulations (see section 13).

If the product contaminates waterways, rivers or sewers, inform appropriate authorities in accordance with statutory procedures.

Avoid ignition points, hot surfaces.

Cleaning methods:

Clean preferably with a detergent, avoid use of solvents.

Use absorbent.

The removal must be performed by a licensed reclaimer.

7 - HANDLING AND STORAGE

The regulations relating to storage premises apply to workshops where the product is handled.

Handling:

Prevent the creation of flammable or explosive concentrations in air and avoid vapor concentrations above the occupational exposure limit values.

Do not spray near a flame or any incandescent material.

Use away from any flame or incandescent point.

Avoid static discharges.

Follow the usage rules of hygiene and safety given the flammability.

Do not use power.

Do not breathe vapors

Follow the rules for use of pressurized containers for hygiene and safety.

Avoid contact with eyes

Do not smoke

Fire:

Use the product in areas from which all naked lights and other sources of ignition and have protected electrical equipment.

Keep container tightly closed and away from heat, sparks and flame.

Do not use tools that cause sparks. Do not smoke.

Deny access to unauthorized persons.

Avoid contact with hot surfaces or points of ignition.

Keep away all electrical appliances in operation.

VAPOR MAY BE HARMFUL IF BURNING

Recommended equipment and procedures:

For personal protection see Section 8.

Observe the precautions on the label and the rules of labor protection.

Avoid inhaling fumes.

Avoid contact with eyes.

Keep in original packaging. Do not pierce or burn even after use.

Follow the usage rules of hygiene and safety.

Storage and handling precautions applicable to pressurized gas.

Use in well ventilated area

Keep aerosols from heat to prevent overpressure. Possibly with cool water.

Prohibited equipment and procedures:

It is forbidden to smoke, eat or drink in areas where the preparation is used.

Never open the packages under pressure.

Do not pierce or burn even after use.

Do not use power.

Storage:

Keep container tightly closed in a dry and well ventilated place.

Keep away from sources of ignition - No smoking.

Pressure vessel. Protect against sunlight and do not expose to temperatures exceeding 50 ° C.

Keep out of reach of children.

Keep only in original container.

Freezing. Do not store outside.

8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Use personal protective equipment according to Directive 89/686/EEC.

Exposure limit values per INRS ED 984 and the French Order 30/06/04:

France	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:	TMP N °:
106-97-8	800	1900	-	-	-	-
Germany	Category:	MAK-ppm:	MAK-mg/m3:	Notes:	Notes:	
106-97-8	IV	1000	2400	-	-	
ACGIH (TLV)	TWA-ppm:	TWA-mg/m3:	STEL-ppm:	STEL-mg/m3:	Notes:	Notes:
106-97-8	800	1900	-	-	-	-
Exposure Limits (2003-2006):						
Germany / AGW	TWA:	TWA:	Passing	Notes		
106-97-8	1000 mg/m3	2400 ml/m3	4 (II)	DFG		
ACGIH / TLV	TWA:	STEL:	Ceiling:	Definition:	Criteria:	
106-97-8	1000 ppm	-	-	-	-	

Respiratory protection:

Do not use in confined spaces and unventilated

Avoid inhalation

Hand protection:

Protective creams may be used for exposed skin, but they should not be applied after contact with the product.

Gloves recommended if prolonged or frequent contact.

Eye protection and face:

Avoid contact with eyes.

Wear goggles.

Provide eye washes in workshops where the product is constantly handled.

In case of contact with eyes, rinse thoroughly.

Consult an eye doctor if sensation of irritation.

Skin Protection:

For more information, see § 11 of SDS - Toxicological information.

If phenomena of intolerance skin, consult a dermatologist.

9 - PHYSICAL AND CHEMICAL PROPERTIES

General information:

Physical State:

Liquid fluid.

Aerosol.

Important information relating to health, safety and environment:

pH of the substance / preparation:

Neutral.

When the pH is possible, its value is

unspecified

Point / boiling range:

100 ° C.

Vapor Pressure:

less than 110kPa (1.10 bar).

Density:

= 1

Water Solubility:

Soluble.

Other information:

Point / melting range:

Not specified

Auto-ignition temperature:

Not specified.

Point / decomposition range:

Not specified.

10 - STABILITY AND REACTIVITY

Any device capable of producing a flame or create a high temperature a metal surface (burners, electric arcs, furnaces ...) will be banned on the premises.

Conditions to avoid:

Freezing.

Avoid static discharges.

Keep away from heat and ignition sources.

Materials to avoid:

STRONG OXIDIZERS

Hazardous Decomposition Products:

DERIVATIVES AS TOXIC OXIDES OF CARBON

11 - TOXICOLOGICAL INFORMATION

No data on the preparation itself is available.

Of substances generally agreed that when applied to the eye of the animal, significant lesions that appear and persist twenty-four hours at least.

In case of inhalation:

A very important inhalation may cause nausea and irritation of mucous membranes.

If swallowed:

If swallowed, consult a physician or contact a poison control center.

In the event of splashes or contact with skin:

The presentation of the product associated with its frequency of use can generate reactive in persons phenomena of intolerance.

In the event of splashes or contact with eyes:

Rinse immediately. If appearance of a sensation of irritation, consult an ophthalmologist

12 - ECOLOGICAL INFORMATION

No ecological data on the product itself is available.

Any leaks in the sewer or watercourse must be avoided.

DO NOT REJECT THE NATURAL ENVIRONMENT

According to the Directive 2006/8/EC:

CAS	CE	
68439-50-9	500-213-3	Alcohol Ethoxylate C12-C14
	LC50 (fish) 96h (mg / l)	1.000000
	IC50 (Algae) 72h (mg / l)	IC50> 0.1

13 - DISPOSAL CONSIDERATIONS

Do not discharge into drains or watercourses.

AEROSOL DO NOT PIERCE OR BURN AFTER USE

SUBMIT AN AUTHORIZED COLLECTOR. REFER TO PREFECTORIAL FORCE.

Waste:

Recycle or dispose of in accordance with prevailing regulations, preferably by a collector or an approved company.

Do not contaminate the soil or water with waste, do not dispose of them in the environment.

Soiled packaging:

Completely empty container. Keep the label (s) on the container.

Give to a certified disposal contractor.

Local Arrangements:

The Waste regulations are codified in the Environmental Code, by Ordinance No. 2000-914 of 18 September 2000 on the legislative part of the environment.

There are the various texts of Article L. To Article L. 541-1 541-50 found in Book V (Prevention of pollution, risks and nuisances), Title IV (Waste), Chapter I (Elimination of waste and material recovery).

14 - TRANSPORT INFORMATION

Transport product in accordance with ADR for road, RID for rail, IMDG for sea and ICAO / IATA for air transport (ADR 2009 - IMDG 2008 - ICAO / IATA 2009).

Classification:

UN1950 AEROSOLS = flammable

ADR / RID	Class	Code	Groupe	Label	Ident.	QL	Available.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	LQ2	190 327 625	E0	2D	
IMDG	Class 2	Group	ETIQ	QL	FS	Available. EQ				
	2.1	SP63	-	SP277	F-D, S-U	63190277	327959	E0		
IATA	Class 2	ETIQ.	Group	Passenger	Passenger	Cargo	Cargo	notes		EQ
	2.1	-	-	203	75 kg	203	150 kg	A145 A153		E0
	2.1	-	-	Y203	30 kg G	-	-	-		E0

15 - REGULATORY INFORMATION

This product is rinsed for cosmetic purposes.

Classification by:

**Extrêmement inflammable**

Specific risks associated with the preparation and safety recommendations:

R 12	Extremely flammable. Use and keep away from flame or ignition source or spark, heat source or operating electrical appliance-No smoking.
S 2	Keep out of reach of children.
S 23	Do not breathe vapors
S 46	If swallowed, seek medical advice immediately and show this container or label. Pressure containel. To protect against sunlight and do not expose to temperatures exceeding 50 ° C. Do not pierce or burn even after use. Do not spray near a flame or any incandescent material.
S 51	Use only in well ventilated areas. Proceed by brief pressure sprays. Do not use for any purpose other than for which it is intended. Avoid contact with eyes. If contact rinse thoroughly with water.

Special provisions:

Flammability test calculated in accordance with Directive 2008/47/EC.

Employees under medical surveillance enhanced by the Labor Code:

Increased medical surveillance for employees engaged in certain activities defined by Article L. 4111-6 and special orders made under:

- Hazardous Chemicals: Order No. 2003-1254, 23/12/2003.

Classified Installations (France):

BPI No.	Designation under	Plan	Radius
1414	Gas flammable gases (filling plant or distribution) 1. facilities filling bottles or containers. 2. loading or unloading facilities serving a deposit of flammable gases subject to authorization 3. facilities refill supplying motors or other appliances with safety devices (gauges and valves)	A A D	1 1 C
1431	Flammable liquids (industrial manufacturing, including processing of petroleum and its derivatives, desulfurization)	A	3
1432	Flammable Liquids (storage tanks manufactured). 1. When the amount of stored flammable liquids mentioned in 1430 is likely to be present: a) Greater than or equal to 50 tons for Class 2. storage of flammable liquids mentioned in 1430: a) representing a total equivalent capacity above 100 m3. b) representing a total equivalent capacity exceeding 10 m3 but less than or equal to 100 m3.	A A D	AS 4 2 C
Plan	A: leave D: statement; S: public easement; C: subject to periodic inspection provided for in Article L. 512-11 of the Environmental Code.		
Radius:	Radius Display in kilometers.		

16 - OTHER INFORMATION

The working conditions of the user we are not known, the information given in this safety data sheet is based on the state of our knowledge and on national and community regulations.

The product should not be used for other purposes than those specified under heading 1 without first obtaining written handling instructions.

There is always the responsibility of the user to take all measures necessary to meet the requirements of local laws and regulations.

The information in this sheet must be regarded as a description of the safety requirements relating to our product and not as a guarantee of the properties thereof.

Text of risk phrases appearing in section 3:

R 12	Extremely flammable.
R 36	Irritating to eyes.
R 38	Irritating to skin.
R 41	Risk of serious damage to eyes.
R 50	Very toxic to aquatic organisms.
R 52	Harmful to aquatic organisms.